

SECOND REGULAR SESSION

HOUSE BILL NO. 996

92ND GENERAL ASSEMBLY

INTRODUCED BY REPRESENTATIVES DUSENBERG (Sponsor), MAYER, GOODMAN, HOLLAND, SCHLOTTACH, MAY, MOORE, WALLACE, MUNZLINGER, EMERY, SHOEMYER, WILDBERGER, KUESSNER, KRATKY, DETHROW, SALVA, McKENNA, HILGEMANN, WALSH, DOUGHERTY, HENKE, SMITH (14), CRAWFORD AND JONES (Co-sponsors).

Read 1st time January 8, 2004, and copies ordered printed.

STEPHEN S. DAVIS, Chief Clerk

3208L.011

AN ACT

To repeal section 307.375, RSMo, and to enact in lieu thereof one new section relating to school bus inspections.

Be it enacted by the General Assembly of the state of Missouri, as follows:

Section A. Section 307.375, RSMo, is repealed and one new section enacted in lieu thereof, to be known as section 307.375, to read as follows:

- 307.375. 1. The owner of every bus used to transport children to or from school in addition to any other inspection required by law shall submit the vehicle to an official inspection station, and obtain a certificate of inspection, sticker, seal or other device annually, but the inspection of the vehicle shall not be made more than sixty days prior to operating the vehicle during the school year. The inspection shall, in addition to the inspection of the mechanism and equipment required for all motor vehicles under the provisions of sections 307.350 to 307.390, include an inspection to ascertain that the following items are correctly fitted, adjusted, and in good working condition:
- (1) All mirrors, including crossview, inside, and outside;
 - (2) The front and rear warning flashers;
 - (3) The stop signal arm;
 - (4) The crossing control arm on public school buses required to have them pursuant to section 304.050, RSMo;
 - (5) The rear bumper to determine that it is flush with the bus so that hitching of rides cannot occur;
 - (6) The exhaust tailpipe shall be flush with or may extend not more than two inches

17 beyond the perimeter of the body or bumper;

18 (7) The emergency doors and exits to determine them to be unlocked and easily opened
19 as required;

20 (8) The lettering and signing on the front, side and rear of the bus;

21 (9) The service door;

22 (10) The step treads;

23 (11) The aisle mats or aisle runners;

24 (12) The emergency equipment which shall include as a minimum, a first aid kit, flares
25 or fuses, and a fire extinguisher;

26 (13) The seats, including a determination that they are securely fastened to the floor;

27 (14) The emergency door buzzer;

28 (15) All hand hold grips;

29 (16) The interior glazing of the bus.

30 2. In addition to the inspection required by subsection 1 of this section, the Missouri state
31 highway patrol shall conduct an inspection after February first of each school year of all vehicles
32 required to be marked as school buses under section 304.050, RSMo. This inspection shall be
33 conducted by the Missouri highway patrol in cooperation with the department of elementary and
34 secondary education and shall include, as a minimum, items in subsection 1 of this section and
35 the following:

36 (1) The driver seat belts;

37 (2) The heating and defrosting systems;

38 (3) The reflectors;

39 (4) The bus steps;

40 (5) The aisles;

41 **(6) The frame.**

42 3. If, upon inspection, conditions which violate the standards in subsection 2 of this
43 section are found, the owner or operator shall have them corrected in ten days and notify the
44 superintendent of the Missouri state highway patrol or those persons authorized by the
45 superintendent. If the defects or unsafe conditions found constitute an immediate danger, the bus
46 shall not be used until corrections are made and the superintendent of the Missouri state highway
47 patrol or those persons authorized by the superintendent are notified.

48 4. The Missouri highway patrol may inspect any school bus at any time and if such
49 inspection reveals a deficiency affecting the safe operation of the bus, the provisions of
50 subsection 3 of this section shall be applicable.